Green Building Project Fact Sheet Beaulieu Residence

(Earth Sheltered/Hydrogen/Solar Electric)

Project	Project Address Owner City Latitude/Elevation	10989 East Tusayan Trail Bryan Beaulieu Scottsdale, Arizona 33° 30' North, 2540 ft above sea level
Team	Architect Builder	R. J. Bacon Company The Construction Zone, Ltd.
General	Floor Area Time Line	4000 ft ² livable, 2907 ft ² covered Construction began in September 2003 and expected to be complete by Summer 2005.
	Minimal Impact Heat Mitigation	 Building designed with minimal impact on site topography. Desert plants and natural features beyond 10' of building footprint and paved areas protected during construction. Driveway and carport is constructed of permeable materials. Non-permeable walkways, uncovered patios, aprons, and driveways cover no more than 40% of the net buildable site area.
	Orientation	 Home is oriented to the south for active and passive solar strategies.
Site Use	Outdoor Living	 Home is designed with outdoor living in shaded courtyards and protected enclosures. Protected outdoor living area(s) is equal to at least 25% of
	Landscaping Water Conservation	 total conditioned (indoor livable) space. Xeriscape is at least 90% of landscaped areas. Non-sprinkler, zoned irrigation system with separate valving. Irrigation controller with rain sensor shut off. Rainwater collection and storage system for irrigation and cooling of outdoor living areas.
	Pollution Prevention	 No chemical herbicides used on site. No chemical pesticides used on site.
	Air Quality	 Utility supplied power on site at start of construction.
Structural Elements	Pollution Prevention Resource Conservation	 Non-asphalt based damp proofing installed at basement and/or retaining walls. Western coal fly ash concrete with min. 18% substituted volume. Floor structure is at least 75% non-solid sawn lumber unless from
		 Floor structure is at least 75% horr-solid sawn lumber unless from certified sustainable source. Roof structure is at least 75% non-solid sawn lumber unless from certified sustainable source. Beams and headers are at least 75% non-solid sawn lumber unless from certified sustainable source. Interior framing is at least 75% non-solid sawn lumber unless from certified sustainable source. Materials from regionally extracted resources. Products from regional manufacturers.

Building Envelope	Energy Conservation	 Use of thermal mass design. Radiant barriers. All exterior doors insulated with min. R-2. Windows have NFRC Solar Heat Gain Coefficient [SHGC] of .40 or less. Exterior shading devices/screens with a shading coefficient of 0.45 or lower on windows.
BL		 Skylights with an NFRC rating of U-0.5 or lower and SHGC of 0.40 or less. South glass has full exterior shading in May, June, and July at noon. Structures and/or landscaping provide summer sun control/shading on min. 50% of east and west wall surfaces.
Heating, Cooling, and Ventilation	Energy Conservation Indoor Environmental Quality	 Evaporative cooling incorporated through site design and outdoor living areas. Computer controlled roof ventilators for airflow intake or exhaust depending on indoor and outdoor monitored conditions. Temperature controlled ceiling fans installed in every room. Stack and cross ventilation enabled through computer controlled operable windows. Passive solar design for winter heating. Ventilation system installed per ASHRAE standards. Passive radon ventilation system installed per EPA guidelines. All fans rated for 1.5 sone or less.
Electrical Power, Lighting, and Appliances	Energy Conservation	 Daylighting allows natural light to enter the house from two sides of rooms in at least half of livable floor area. No recessed lights in insulated ceilings. At least 50% of total numbers of fixtures are non-incandescent. Maximum interior lighting wattage does not exceed 0.5 watts/square foot. Smart wiring system for lighting controls. Energy Star rated appliances. Gas dryer stub-out. Solar electric lighting for at least half of site lighting. Photovoltaic (8kW) solar electric power system with adjustable tilt for seasonal solar (altitude) angles. Hydrogen generating fuel cells (8kW) powered by solar electric.
Plumbing System	Water and Energy Conservation	 Water heater within 20-pipe feet length of bathroom fixtures. Whole house insulated hot water recirculation system. Southern exposed roof area provided with plumbing for solar hot water system. Dual flush control toilets. Two pipe drain system for graywater recovery system.
Roofing	Resource Conservation	High durability/low maintenance earth sheltered roof system with min. 25% recycled content roof membrane and native desert vegetation.

Exterior Finishes	Resource Conservation	 Locally derived materials. Regionally quarried and processed or cultured stone. Materials left in natural state.
Interior Finishes	Indoor Air Quality	 Only low toxic, solvent-free adhesives, mastics, and sealants used for at least 75% of the home. Water based finishes on floors.
Interior Doors,	Resource Conservation	 No tropical woods used. No wood base, cove, or door/window trim used.
Finish	Resource Conservation Indoor Air Quality	 Exposed stained concrete flooring. Rapidly renewable flooring materials. Combined hard flooring is 100% of conditioned floor area.
Pools and Spas	Energy and Water Conservation Occupant Health	 Solar assisted pool and spa heating/cooling system. Retractable pool cover. Low-chlorine pool filtration system. Pool has zero water loss backwash system.
Solid Waste	Resource Conservation	Recycling and composting system.

Rev. 5/9/05